

## INDUSTRIAL REMOTE CONTROL

Control Chief has established a new standard in the wireless industrial control market. This radio is an outstanding value, featuring a compact, 12-button transmitter and a full complement of safety features. The pre-wired receiver makes installation and set-up simple.



800-233-3016 814-362-6811 Fax: 814-368-4133

www.controlchief.com

Control Chief Corporation 200 Williams Street Bradford, PA 16701




## FEATURES & BENEFITS

- Puts operator in total control of equipment from plant floor
- Long range operation of up to 1000 ft. (8 power settings available)
- Red Mushroom push-button (mainline contractor control)
- Prewired receiver for quick installation
- Two (2) speed (SK2500) 5 motion models
- 25KHz channel spacing

- IP65 rated glass reinforced nylon enclosures
- TX power consumption = 28mA
- (U) Power Indicator on RX for troubleshooting ease
- Operation frequency: 430 ~ 435 MHz fully compliant with FCC Part 15 un-licensed and CE European directive (non-licensed system)
- Start up/Shut down
  (No external alarm needed)
- Available in AC or DC power

## **ACCESSORIES**



Transfer Switch



Protective Transmitter Cover



Copy Module



Dipole Antenna Kit



# **TECHNICAL SPECIFICATIONS**

### **Overall Specifications**

Operating Channels	70
ID Codes	Over one million sets
Channel Space	25 KHz
Hamming Distance	≥4
Structure	Enhanced Glass-Fiber
Operating Environment	-40°C ~ +85°C
Operating Distance	Up To 300 M

#### Receiver Specifications

Multiple Supply Voltages	Available in AC or DC power
Weight	2900 g(K3/K4) w/ cable
Dimensions	6.67" × 4.4" × 10.8" (L × W × H)

#### Transmitter Specifications


Emission Power	< 10mW
Dimensions	3.17" × 2.37" × 10.91" (L × W × H)
Weight	385 g (K3/K4)
Battery	Four (4) Standard AA Alkaline

<sup>\*</sup> Dimensional drawings available upon request.

PRODUCT SPECIFICATIONS ARE FOR REFERENCE ONLY. SUBJECT TO CHANGE WITHOUT NOTICE. CONTACT CONTROL CHIEF FOR VERIFICATION.



#### Wiring Diagram



Wiring diagrams for reference only - not for installation





